VVA-17 | Flat vacuum cups with shank

Diameter 17mm, with or without support, rubber

RoHS

MATERIAL

Vacuum cup in oil-proof rubber (NBR), natural (NR), or silicone (VMQ).
AVP nickel-plated bracket.

STANDARD EXECUTIONS

- **VVA-17-A**: oil-proof rubber, without support.
- **VVA-17-N**: natural rubber, without support.
- **VVA-17-S**: silicone rubber, without support.
- **VVA-17-T-A**: oil-proof rubber, with support.
- **VVA-17-T-N**: natural rubber, with support.
- **VVA-17-T-S**: silicone rubber, with support.


FEATURES AND APPLICATIONS

They are specifically intended for the packaging sector, where there is a need to handle lightweight, thin objects. Particularly in plastic film packaging and for opening bags. The flexible lip allows the vacuum cup to adapt to various types of packaged products, including fragile ones. The grooves on the vacuum cup's contact surface ensure a more effective grip on the product to be handled; in particular, they allow even distribution of the vacuum on the surface of the product, preventing the packaging sheet or bag from being sucked into the vacuum cup. They are also used in the paper converting industry, for handling sheets of paper.
See Technical Data for vacuum cups.






VVA-17



VVA-17-T



VVA-17-A

Code	Description	d	d_1	d_2	h	h_1	F* [Kg]	Volume # [mm3]	⚖
VV.45003	VVA-17-A	17	3.8	9	11	1	0.6	213	1

VVA-17-N

Code	Description	d	d_1	d_2	h	h_1	F* [Kg]	Volume # [mm3]	⚖
VV.45004	VVA-17-N	17	3.8	9	11	1	0.6	213	1

VVA-17-S

Code	Description	d	d_1	d_2	h	h_1	F* [Kg]	Volume # [mm3]	⚖
VV.45005	VVA-17-S	17	3.8	9	11	1	0.6	213	1

VVA-17-T-A

Code	Description	d	d_1	d_2	h	h_1	h_2	h_3	h_4	l	F* [Kg]	Volume # [mm3]	⚖
VV.45006	VVA-17-M5-T-A	17	M5	9	19.5	1	11	4.5	4	8	0.6	213	4

VVA-17-T-N

Code	Description	d	d_1	d_2	h	h_1	h_2	h_3	h_4	l	F* [Kg]	Volume # [mm3]	⚖
VV.45007	VVA-17-M5-T-N	17	M5	9	19.5	1	11	4.5	4	8	0.6	213	4

VVA-17-T-S

Code	Description	d	d_1	d_2	h	h_1	h_2	h_3	h_4	l	F* [Kg]	Volume # [mm3]	⚖
VV.45008	VVA-17-M5-T-S	17	M5	9	19.5	1	11	4.5	4	8	0.6	213	4

* The force of the vacuum cups indicated in the table represents 1/3 of the value of the theoretical force calculated at a vacuum level of -75 KPa and a safety coefficient of 3.# Indicates the internal geometric volume of the vacuum cup and represent

Models all rights reserved in accordance with the law. Always mention the source when reproducing our drawings and photos.